



**2840 litres (625 imp.gal.)
Standard Two Piece
Septic Tank**

Details

Concrete Strength: 6500 psi (45 MPa) @ 28 Days
Air Entraining: 5 - 7%
Reinforcement: 10 mm Rebar and Structural Fiber
Joint Seal: Butyl Rope Sealant Or Equivalent
Design For Earth Dead Load Only
Maximum Burly: 2.0 m (6.5')
Conforms To CSA B66-M2005

Options

24" Diameter Poured In Place Plastic Riser And Cover On Inlet End
Alternative Placement Of Inlet And Outlet Holes
Plastic or Concrete Risers
Special Order Single Compartment

Other Notes

100 mm (4") Pipe Baffles Supplied
Weight: 6600 lb (2012 kg)
Conforms To CSA B66M05 (Dalhousie University)

**ISLAND
CONCRETE PRODUCTS LTD.**
SYDNEY SITE
517 KELTIC DR.
Phone: 902-562-2426
PORT HASTINGS SITE
522 Hwy 105
Toll Free: 1-855-562-2426

**BROOKFIELD
CONCRETE PRODUCTS LTD.**
P. O. BOX 37, 778 Hwy 2
BROOKFIELD, N. S.
B0N 1C0
Phone: 902-673-2225
Toll Free: 1-888-705-2225
Fax: 902-673-2255

DATE: March 2016
SCALE: 3/8" = 1'-0"
PROJECT:
LOCATION: Sheet # of

Brookfield Concrete Products Ltd.
Your Pre-cast Specialists

e-mail: info@brookfieldconcrete.ca

Island Concrete Products Ltd.
Sydney / Port Hastings

e-mail: info@islandconcreteproducts.ca