



**1500 litres (330 imp. gal.)  
One Piece Pump  
Chamber**

### Details

Concrete Strength: 6500 psi (45 MPa) @ 28 Days  
Air Entraining: 5 - 7%  
Reinforcement: 10 mm Rebar and Structural Fiber  
Joint Seal: Butyl Rope Sealant Or Equivalent  
Design For Earth Dead Load Only  
Maximum Sully: 2.0 m (6.5')  
Conforms To CSA B66-M2005

### Options

Alternative Placement Of Inlet And Outlet Holes  
Plastic Risers

### Other Notes

Pump Drawdown- 63 litres (14 imp.gal) Per Inch  
Weight: 4994 lb (2265 kg)  
Conforms To CSA B66M05  
(Dalhousie University)

**ISLAND  
CONCRETE PRODUCTS LTD.  
SYDNEY SITE**

517 KELTIC DR.  
Phone: 902-562-2426  
PORT HASTINGS SITE  
522 Hwy 105  
Toll Free: 1-855-562-2426

**BROOKFIELD  
CONCRETE PRODUCTS LTD.**

P. O. BOX 37, 778 HWY 2  
BROOKFIELD, N. S.  
B0N 1C0  
Phone: 902-673-2225  
Toll Free: 1-888-705-2225  
Fax: 902-673-2255

DATE: March 2016  
SCALE: 3/8" = 1'-0"  
PROJECT:  
LOCATION: Sheet # of

**Brookfield Concrete Products Ltd.**  
**Your Pre-cast Specialists**

e-mail: [info@brookfieldconcrete.ca](mailto:info@brookfieldconcrete.ca)

**Island Concrete Products Ltd.**  
**Sydney / Port Hastings**

e-mail: [info@islandconcreteproducts.ca](mailto:info@islandconcreteproducts.ca)